

North American Hydraulics,
(NAHI, LLC), partnering with
Bonfiglioli gearboxes.

Features and Benefits:

- Compact and rugged design
- High torque and load capabilities
- Mechanical lifetime seals
- Rotating housing
- Available with failsafe parking brake, hydraulically released on request

Proven Solutions for:

- Agriculture / Forestry
- Mining / Oil and Gas
- Construction / Industrial
- Marine / Utility
- Waste and Material Handling
- Railway



Please contact NAHI for additional information.

The above information should be used as a guide and is subject to change without notice.

Please contact NAHI for proper selection.



Gear Boxes - Bonfiglioli 700C Series

Type	Torque (Nm)	Range of Ratios 1:	Max Input Speed rpm	Hydraulic Motor Drive inline	Braking Torque Right angle (Nm)	Min. Opening Pressure (bar)	Version	Weight (kg)
700 C1 H	1,000	5.25	1000	LS	140 – 250	15 – 25	S	20
701 C1	2,200	6.2	1000	LS	250 – 350	20 – 30	S	25
703 C2 H	4,000	19-40	3500	HS	210	18	S	42
705 C2 H	10,000	22-53	3500	HS	220 – 310	10 – 20	S	60
706 C3 B	18,000	68-173	3500	HS	250 – 500	10 – 20	S	95
707 C3 B	26,000	55-120	3500	HS	250 – 500	10 – 20	S	135
709 C3 B	30,000	55-147	3500	HS	250 – 600	10 – 20	S	180
710 C3 B	36,000	55-166	3500	HS	250 – 600	10 – 20	S	200
711 C3 B	45,000	71-163	3500	HS	400 – 800	10 – 20	S	270
713 C3 B	60,000	56-147	3000	HS	450 – 800	10 – 20	S	310
715 C3 B	85,000	62-156	3000	HS	600 – 1000	10 – 20	S	350
716 C3 B	100,000	83-174	3000	HS	800 – 1200	10 – 20	S	400
717 C3 H	130,000	92-211	3000	HS	800 – 1200	10 – 20	S	630
718 C3 H	180,000	87-263	3000	HS	800 – 1400	10 – 20	S	750
720 C3 H	220,000	175-287	3000	HS	800 – 1700	10 – 20	S; C	820
722 C3 H	330,000	296-492	3000	HS	1500 – 2500	15 – 30	S	1300
724 C4 H	450,000	350-428	3000	HS	1500 – 2500	15 – 30	S; C	1300
726 C4 H	625,000	248-282-330	3000	HS	2 x 1200	27	S; C	2800

LS = Low Speed Motor / HS = High Speed Motor

