

North American Hydraulics, (NAHI, LLC), partnering with Donaldson offering hydraulic filters and accessories to keep sophisticated heavy-duty mobile equipment running smoothly.

Features and Options:

- Low Pressure Filters, the most common type of filter in hydraulic circuits, rated for working pressures up to 350 psi. In-tank and in-line configurations are available to accommodate virtually any application.
- Medium Pressure Filters, offered in both spin-on and in-line cartridge-style can be used in applications up to 2000 psi. Duramax Filters are the highest rated medium pressure spin-on filters available.
- High Pressure Filters help protect critical components from catastrophic failure, rated for working pressures up to 6500 psi. Various porting sizes and types, including manifold style, are available.

Benefits:

- Reliable
- Long Lived
- Easy to Install

Please contact NAHI for additional information.

The above information should be used as a guide and is subject to change without notice.

Please contact NAHI for proper selection.

Filtration Solutions Engineered for All Types of Equipment



Hydraulic Filtration Solution Providers



Comprehensive Hydraulic Filtration

Model Series	Max Flow gpm	Max Pressure psi	Porting Size Options
LOW PRESSURE - Spin-On Filters			
SP15/25	30	150	1/2", 3/4" NPT, SAE-8, -12 O-ring
W023	60	150	1 1/4" NPT, SAE-20 O-ring
HBK05	60	150	1 1/4" NPT, SAE-20 O-ring
SP50/60	60	150	1 1/4" NPT, SAE-20 O-ring
SP80/90	100	150	1 1/2" NPT, SAE-24 O-ring, 2" SAE 4-Bolt Flange Code 61
SP100/120	100	150	1 1/2" NPT
TT15/30/60	50	100	3/4", 1 1/2" NPT
LOW PRESSURE - In-Tank Filters			
WL15	50	200	SAE-24 O-ring, 1 1/2" SAE 4-Bolt Flange Code 61
WL16	200	200	1 1/2" NPT, SAE-24 O-ring, 1 1/2" SAE 4-Bolt Flange Code 61
Fik	170	145	1/2" NPT, 3/4" NPT, 1" NPT, SAE-8, -12, -16, -20, -24 O-ring, 2" SAE 4-Bolt Flange Code 61
SRK Combo	79	145	Inlet: SAE-16, -20 O-ring, Outlet: SAE-16 O-ring
LOW PRESSURE - In-line Cartridge Filters			
HRK10	300	150	4" ANSI Flange, 8-bolt 150#
MEDIUM PRESSURE - Spin-on Filters			
HMK03	25	1000	SAE-12 O-ring
HMK04	35	500	3/4", 1" NPT, SAE-12, -16 O-ring
HNK04	35	500	SAE-12, -16 O-ring
HMK05	50	350	1 1/4" NPT, SAE-20 O-ring
HNK05	50	350	SAE-20 O-ring
HMK24	60	500	SAE-20 O-ring, 1 1/4" SAE 4-Bolt Flange Code 61
HMK25	100	350	1 1/2" NPT, SAE-24 O-ring, 1 1/2" SAE 4-Bolt Flange Code 61
MEDIUM PRESSURE - In-line Cartridge Filters			
FLK90	40	580	SAE-12, -16 O-ring
FLK110	42	435	SAE-20 O-ring
FLK125	85	508	2" SAE 4-Bolt Flange Code 61
DPK350	100	350	1 1/2" SAE 4-Bolt Flange Code 61
W061	100	600	SAE-12, -16, -20 O-ring
HDK06	150	350	2 1/2" NPT
W041	300	500	SAE-24 O-ring, 2" or 2 1/2" SAE 4-Bolt Flange Code 61
HFK08	300	350	3" NPT, SAE-20 O-ring
HIGH PRESSURE - In-line Cartridge Filters			
HPK02	20	2000	SAE-12 O-ring
DPK2400	100	2400	1 1/2" SAE 4-Bolt Flange Code 61
W440	20	4000	SAE-12 O-ring or Manifold Mounting
FPK02	25	6090	SAE-12 O-ring
W350	50	3000	SAE-12, -16 O-ring
HPK03	60	3000	SAE-12, -16 O-ring
FPK04	100	4350	SAE-20 O-ring
HPK04	120	6000	SAE-20 O-ring, 1 1/4" or 1 1/2" SAE 4-Bolt Flange Code 61 or 62
W451	150	4500	SAE-24 O-ring, 1 1/2" SAE 4-Bolt Flange Code 61 or 62, Manifold Mounting
W620	150	6000	SAE-16, -20, -24 O-ring, 1 1/4" SAE 4-Bolt Flange Code 62, 1 1/2" SAE 4-Bolt Flange Code 61
HPK05	200	3000	2" SAE 4-Bolt Flange Code 61



Performance Under Pressure

NAHI, LLC – CUSTOMER SERVICE • 225-751-0500 • www.nahi.com

Filter Housing Style Code

 Spin-on
  In-tank Housing / Cartridge
  In-line Housing / Cartridge

