


North American Hydraulics, (NAHI, LLC), partnering with Hydro Leduc hydraulic pumps.



Features and Options:

- Compact size
- Pump automatically sets to required direction of rotation
- High mechanical resistant materials
- Reinforced sealing
- Relatively high rotating speeds with seven pistons
- Plate barrel synchronization
- Dual direction of rotation



Proven Solutions for:

- Material Handling / Construction
- Utility Machines / Agriculture
- Forestry / Marine



Please contact NAHI for additional information

The above information should be used as a guide and is subject to change without notice.

Please contact NAHI for proper selection.



XAi Series Intelligent Pumps – Fixed Displacement Bent Axis Design								
Model	Displacement		Rated Pressure psi	Peak Pressure psi	Max Speed rpm	Shaft Output	Mounting Output	Wgt lbs
	in ³	cc						
XAi 18	1.10	18.0	5,510	6,090	2,900	SAE B2B or SAE B4B	7/8"-13T	22.5
XAi 25	1.52	25.0			2,750			
XAi 32	1.95	32.0			2,700			
XAi 41	2.50	41.0			2,550			
XAi 50	3.07	50.3			2,450	SAE B4B	1"-15T	
XAi 63	3.84	63.0			2,300			

TXVA Series Pumps with Load Sensing Control – SAE Version							
Model	Displacement in ³	Rated Pressure psi	Peak Pressure psi	Max Speed rpm	Shaft Output	Mounting Output	Wgt lbs
TXVA 92	5.60	5,500	5,800	1,900			

